

Product Technical Data Sheet

FS-290LC POLYAMINE

Fast Setting Epoxy Curing Agent

APPLICATIONS

- Construction Adhesives
- Solvent Free
High Solids Coatings
- Crack Injection Resin
- Accelerate Flooring Systems
- Hardened Concrete Adhesives

FEATURES AND BENEFITS

- Does not contain Nonyl Phenol
- Does not contain Benzyl Alcohol
- Does not contain TMD
- Economical
- Low Viscosity
- Fast Setting
- High Strength
- Excellent Damp Adhesion
- Excellent Color Stability
- Low Color



3835 State Route 72
Kirkland, Illinois 60146

www.epoxychemicals.com

Phone: 815-522-2308

FAX: 815-522-9041

e-mail: info@epoxychemicals.com

FS-290LC POLYAMINE is a modified polyamine for use as a curing agent for liquid epoxy resin. Additionally it can be used to accelerate other hardener systems to improve thin film cure. Demonstrates excellent thin film development at low temperatures with good film appearance and low color properties.

FS-290LC POLYAMINE Properties

Appearance:	Straw Liquid
Viscosity(cps)	150- 225
Density(lbs/gal):	8.4
Equivalent Weight:	75
PHR, L.E.R.	40

Typical Performance Properties

Liquid Epoxy Resin	100
FS-290LC POLYAMINE	40
Gel Time (150g.), mins	11
Tack Free, 10 mils, hours	
@ 75 F	1.5
@ 45 F	4.5
Thin Film Set, 10 mils, hours	
@ 75 F	2.5
@ 45 F	6
Compressive Strength (ASTM D695)	
psi, 7 Days (neat resin)	12,700
Tensile Strength (ASTM D638)	
psi, 7 Days (neat resin)	10,800
Chemical Resistance	
Gasoline	Sulfuric Acid
Hydrochloric Acid	Sodium Hydroxide
Xylene	

Data presented are typical laboratory values.

Product Technical Data Sheet



DISPOSAL: Collect with absorbent material. Dispose of in accordance with current local, state and federal regulations

FIRST AID: In case of skin contact, wash immediately and thoroughly with soap and water. For eye contact, flush immediately with plenty of water for at least 15 minutes. Consult physician immediately. For respiratory problems, remove person to fresh air.

ENVIRONMENTAL SAFETY PRECAUTIONS: (Industrial Use Only) Corrosive. Contains amines. Contact with eyes or skin may cause severe burns. Can cause sensitization after prolonged or repeated use. Use of safety goggles and chemical resistant gloves is highly recommended. Use with adequate ventilation.

WARRANTIES: Seller warrants that the Products do not infringe upon any copyright, patent, or trademark or trade secret, nor violate the proprietary information rights of any third party. Seller warrants that its Products will conform to and perform in accordance with the Products' specifications. THE FOREGOING WARRANTIES, ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. **LIMITATION ON LIABILITIES:** Because of the difficulty of ascertaining and measuring damages hereunder, it is agreed that, except for claims for bodily injury. Seller's liability to the Buyer or any third party, for any losses or damages, whether direct or otherwise, arising out of the purchase of Product from Seller by Buyer shall not exceed the total amount billed and billable to the Buyer for the Product hereunder. **IN NO EVENT WILL SELLER BE LIABLE FOR ANY LOSS OF PROFITS OR OTHER SPECIAL OR CONSEQUENTIAL DAMAGES, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.**